

View Online at <https://aerobasegroup.com/nsn/5935-01-097-4246>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 1.156 inches and 1.187 inches

**Overall Diameter:**

Between 0.344 inches and 0.391 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Cable Entrance Diameter:**

0.155 inches

**Distance From Mounting Shoulder To Front Face:**

0.425 inches

**Mounting Facility Thickness:**

0.093 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

5000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

75.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.312 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy 360 single mating end single contact grouping

**Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-c-14550, cl 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, cl 2 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy 360

**Shell Surface Treatment:**

Copper

**Shell Surface Treatment Specification:**

Mil-c-14550, cl 4 military specification single treatment response

**Shell Material Specification:**

Qq-b-626 federal specification single material response

**Insert Material Specification:**

L-p-403 federal specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-14550 spec.