Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-097-4262

Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

4.350 inches

Overall Height:

0.655 inches

Overall Width:

0.359 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

4.100 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end or plastic phenolic single mating end

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-p-19833 military specification single material response single mating end or mil-m-14 military specification single material response single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 70 single mating end single contact grouping **Included Contact Type:**

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-left handandjackscrew type-female and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.070 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.