

View Online at <https://aerobasegroup.com/nsn/5935-01-097-4265>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

3.350 inches

**Overall Width:**

0.655 inches

**Body Height:**

0.250 inches

**Environmental Protection:**

Vibration resistant and salt water resistant and shock resistant and humidity resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

3.100 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Jackscrew type-male and location-left hand and jackscrew type-female and location-right hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.