Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-097-5897

Body Style: Straight shape, flush mount **Overall Length:** 1.634 inches **Overall Height:** Between 3.060 inches and 3.090 inches **Overall Width:** Between 1.985 inches and 2.015 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.122 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.783 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.438 inches **Distance From Mounting Shoulder To Front Face:** Between 0.055 inches and 0.065 inches Mating End Quantity: 2 **Contact Position Arrangement Style:** "106, a106" all mating ends **Contact Removability:** Removable all mating ends all contact groupings **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Gold all mating ends all contact groupings **Insert Material:** Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response all mating ends all contact groupings **Terminal Type:** Crimp all mating ends all contact groupings **Shell Material:** Aluminum alloy

NSN 5935-01-097-5897

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 type 2 federal specification 1st treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response all mating ends or 1288 bx mfr ref single material response all mating ends

Included Contact Quantity:

106 1st mating end single contact grouping

Included Contact Type:

Round socket all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.212 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-81659/35 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard):

Mil-g-45204 spec.