Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-097-6647

Thread Class:	
2a Thread Direction:	
Right-hand	
Overall Length:	
0.947 inches	
Overall Height:	
1.310 inches	
Overall Width:	
1.310 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.062 inches	
Distance From Mounting Shoulder To Front Face:	
0.322 inches	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
18-32 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
7.5 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
600.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
850.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet pin	
Thread Size:	
1.062 inches	
Terminal Location:	
Back single mating end single contact grouping	

## NSN 5935-01-097-6647

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass fiber single mating end and plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A039b0