

View Online at <https://aerobasegroup.com/nsn/5935-01-097-8074>

Body Style:

Rectangular shape, center screwlock

Overall Length:

1.675 inches

Overall Height:

1.070 inches

Overall Width:

0.830 inches

Distance Between Mounting Facility Centers:

1.300 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type i, grade c or d military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.