Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-098-1590

#### **Body Style:**

Straight shape, external coupling

# **Overall Length:**

1.009 inches

# **Overall Height:**

1.328 inches

# **Overall Width:**

1.328 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

# **Unthreaded Mounting Hole Diameter:**

#### 0.120 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

# Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

18-53 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

330.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# NSN 5935-01-098-1590

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

#### Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Included Contact Quantity:

53 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material:**

Gold and silver

# **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

96906-ms27497 government standard

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-c-38999 spec.