Plastic diallyl phthalate single mating end

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-098-2035

Thread Class:
2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.719 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 2.135 inches and 2.145 inches
Overall Height:
0.875 inches
Overall Width:
0.781 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.469 inches
Threaded Device Type:
Mounting hole and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
12 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Spring friction
Thready Qty Per Inch (tpi):
56 and 32
Thread Size:
0.086 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic dially/ phthalato single mating and



Contact Surface Treatment Specification:

Mil-g-45204 ty ii, cl 1 grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 cl 4

military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626 comp 11 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end or mil-m-14 ty gd1-30 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.