NSN 5935-01-098-6269

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-098-6269

| Body Style: |
|--|
| Straight type |
| Overall Length: |
| 3.295 inches |
| Overall Height: |
| 0.949 inches |
| Overall Width: |
| 0.490 inches |
| Environmental Protection: |
| Vibration resistant and shock resistant and salt water resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.122 inches |
| Distance Between Mounting Facility Centers: |
| 2.975 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Tin single mating end single contact grouping and nickel single mating end single contact grouping and gold single mating end single contact |
| grouping |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 1, grade c, cl 1 military specification 2nd treatment response single mating end single contact grouping |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Insert Material Specification: |
| Mil-p-46161, grade b, cl 15 military specification single material response single mating end |
| Included Contact Quantity: |
| 60 single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |

Gold

0.060 gold grains, troy **Precious Material:**

NSN 5935-01-098-6269

Electrical Receptacle Connector - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Shelf Life:

Mil-std (military Standard): Mil-g-45204 spec.