Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-0015

Body Style:

Straight type

**Overall Length:** 

3.500 inches

## **Overall Height:**

0.465 inches

**Overall Width:** 

0.350 inches

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches

## Mating End Quantity:

1

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### Polarization Method:

Guide pin/socket

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal

specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## Guide Design And Location:

D shape pin left-hand at 12 oclock and d shape socket right-hand at 12 oclock

## Insert Material Specification:

Mil-m-14, ty gdi-30f or sdg-f military specification single material response single mating end

## Included Contact Quantity:

80 single mating end single contact grouping

# Included Contact Type:

Round socket single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold



**Precious Material And Weight:** 

0.080 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.