## NSN 5935-01-099-0268

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-0268

**Overall Length:** 

Between 8.270 inches and 8.330 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.800 inches

**Overall Height:** 

0.627 inches

**Overall Width:** 

Between 1.720 inches and 1.780 inches

**Environmental Protection:** 

Cold resistant and heat resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.198 inches and 0.204 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

**Mating End Quantity:** 

1

**Contact Removability:** 

Nonremovable single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic polyamide single mating end

**Terminal Type:** 

Wire wrap single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

**Shell Surface Treatment:** 

Anodize

**Shell Surface Treatment Specification:** 

Mil-a-8625, cl 2 military specification single treatment response

**Shell Material Specification:** 

Qq-a-250/11 federal specification single material response

**Insert Material Specification:** 

Mil-m-20693, type 1 military specification single material response single mating end

## NSN 5935-01-099-0268

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

160 single mating end single contact grouping

**Included Contact Type:** 

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.160 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-20693 spec.