Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-0409

Thread Class: 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 1.247 inches **Overall Height:** 1.031 inches **Overall Width:** 1.031 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** 0.447 inches **Threaded Device Type:** Back shell Mating End Quantity: 1 **Contact Position Arrangement Style:** 13-98 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches

AeroBase Group

Terminal Locati	
Back single mati	ng end single contact grouping
Contact Materia	al:
Copper alloy sing	gle mating end single contact grouping
Contact Surface	e Treatment:
Gold single mati	ng end single contact grouping
Contact Surface	e Treatment Specification:
Mil-g-45204 milit	ary specification single treatment response single mating end single contact grouping
Terminal Type:	
Solder well single	e mating end single contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface T	reatment:
Cadmium and ni	ckel
Included Conta	ct Quantity:
10 single mating	end single contact grouping
Included Conta	ct Type:
Round socket sir	ngle mating end single contact grouping
Special Feature	IS:
Contact designation	tion 12-98
Precious Materi	ial And Location:
Contact surfaces	s gold
Precious Materi	ial And Weight:
0.010 gold grains	s, troy
Precious Materi	ial:
Gold	
Thread Series D	Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Measure	e:
Demilitarization	
No	
Fiig:	
A039b0	
Mil-std (military	y Standard):
Mil-g-45204 spec	C