Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-0994

### Body Style:

Angle shape, external coupling

### **Overall Length:**

1.093 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.531 inches

#### **Overall Height:**

0.921 inches

#### **Overall Width:**

0.750 inches

#### Environmental Protection:

Shock proof and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

#### 0.140 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

# 0.531 inches

\_\_\_\_

Flange Length:

0.750 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Bnc single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

### **Included Contact Quantity:**

1 single mating end single contact grouping

# **Bushing Accommodation Hole Shape:**

Round

#### **Included Contact Type:**

Coaxial socket single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.