NSN 5935-01-099-0994

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-0994

view Online at https://aerobasegroup.com/nsn/5935-01-099-0994
Body Style:
Angle shape, external coupling
Overall Length:
1.093 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.531 inches
Overall Height:
0.921 inches
Overall Width:
0.750 inches
Environmental Protection:
Shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.531 inches
Flange Length:
0.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Side single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round

rtouria

Included Contact Type:

Coaxial socket single mating end single contact grouping

NSN 5935-01-099-0994

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.