# NSN 5935-01-099-2594

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-2594

### Body Style:

T-shape

**Overall Length:** 

1.530 inches

## **Overall Height:**

1.050 inches

## **Overall Width:**

0.540 inches

#### **Environmental Protection:**

Corrosion resistant and moisture proof and shock proof and vibration proof

#### Mating End Quantity:

3

#### **Contact Position Arrangement Style:**

C all mating ends

**Contact Removability:** 

Nonremovable all mating ends single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends single contact grouping

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

**Contact Material:** 

Copper alloy all mating ends single contact grouping

### **Contact Surface Treatment:**

Silver all mating ends single contact grouping

#### **Insert Material:**

Plastic tetrafluoroethylene all mating ends

### **Contact Material Specification:**

Qq-b-530 federal specification single material response all mating ends single contact grouping

#### **Shell Material:**

Copper alloy 360

#### Shell Surface Treatment:

Silver

### Shell Surface Treatment Specification:

Qq-s-365a federal specification single treatment response

## **Shell Material Specification:**

Qq-b-626 federal specification single material response

#### **Included Contact Quantity:**

1 all mating ends single contact grouping

### **Included Contact Type:**

Coaxial socket all mating ends single contact grouping

## NSN 5935-01-099-2594

Connector Adapter - Page 2 of 2



Precious Material And Location: Contact and body surfaces silver Precious Material And Weight: 0.115 silver grains, troy Precious Material: Silver Shelf Life: N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0