

View Online at <https://aerobasegroup.com/nsn/5935-01-099-4941>

Body Style:

Straight shape, internal coupling

Overall Length:

0.838 inches

Overall Diameter:

0.378 inches

Environmental Protection:

Moisture resistant and shock resistant and thermal shock resistant and vibration resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 2nd mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

180.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Contact Surface Treatment:

Gold all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-g 45204, type 2, cl 2 military specification single treatment response all mating ends all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

spec.