NSN 5935-01-099-8271

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-099-8271

Body Style:
Straight shape, external coupling
Overall Length:
0.701 inches
Overall Height:
1.141 inches
Overall Width:
1.141 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Distance From Mounting Shoulder To Front Face:
Between 0.442 inches and 0.447 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-35 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-099-8271

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Shell Material Specification:
Qq-a-225 federal specification single material response
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26074 spec.