NSN 5935-01-100-4849

Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-4849

Body Style:
Straight shape
Overall Length:
1.260 inches
Overall Height:
1.170 inches
Overall Width:
4.325 inches
Environmental Protection:
Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height: 0.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
3.875 inches
Distance From Mounting Shoulder To Front Face:
0.528 inches
Mating End Quantity:
1 Contact Position Arrangement Style:
Contact Position Arrangement Style:
64 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
2 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Nickel single mating end single contact grouping and copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

NSN 5935-01-100-4849

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location:
D shape pin left-hand bottom at 6 oclock and d shape pin right-hand top at 6 oclock
Shell Material:
Aluminum alloy 380.0
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, cl 1 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
64 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.064 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.