NSN 5935-01-100-5488

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-5488

Body Style:

Rectangular shape, angle

Overall Length:

Between 2.714 inches and 2.744 inches

Overall Height:

0.729 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-01-100-5488

Electrical Receptacle Connector - Page 2 of 2



**	
Metal	
Shell Surface Treatment:	
Cadmium and chromate	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, class 2 federal specification all treatment responses	
Insert Material Specification:	
Mil-m-14, type sdg-f military specification 1st material response single mating end or mil-m-24519, type gpt-30f or type get-30f mil	litary
specification 2nd material response single mating end	
Included Contact Quantity:	
37 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Special Features:	
Pin terminal diameter 0.027 min to 0.033 max	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.037 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	cation
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	I
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-c-24308/24 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	