Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-5815

| _ | |
|---|--|
| | Body Style: |
| | itraight shape |
| | Overall Length: |
| | .906 inches |
| | Overall Height: |
| - | .890 inches |
| - | Overall Width: |
| | .438 inches |
| - | Inable To Decode: |
| - | Inable to decode and unable to decode |
| | invironmental Protection: |
| - | hock resistant and vibration resistant |
| N | lating End Quantity: |
| 1 | |
| | contact Position Arrangement Style: |
| | 5 single mating end |
| C | Contact Removability: |
| | Ionremovable single mating end single contact grouping |
| | contact Maximum Current Rating In Amps: |
| | .0 single mating end single contact grouping |
| C | Contact Maximum Dc Voltage Rating In Volts: |
| 2 | 50.0 single mating end single contact grouping |
| Т | erminal Location: |
| S | ide single mating end single contact grouping |
| C | Contact Material: |
| C | Copper alloy single mating end single contact grouping |
| C | Contact Surface Treatment: |
| Ģ | Gold single mating end single contact grouping |
| h | nsert Material: |
| F | Plastic polyamide single mating end |
| C | Contact Surface Treatment Specification: |
| Ν | Ail-g-45204, type 2, class 1, grade c military specification single treatment response single mating end single contact grouping |
| Т | erminal Type: |
| F | in single mating end single contact grouping |
| h | nsert Material Specification: |
| Ν | fil-m-19887, type 610 military specification single material response single mating end |
| h | ncluded Contact Quantity: |
| 2 | 5 single mating end single contact grouping |
| h | ncluded Contact Type: |
| F | cound socket single mating end single contact grouping |
| S | pecial Features: |
| F | urnished items - potting form |
| | |



Precious Material And Location:

Contact and terminal surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.