## NSN 5935-01-100-7016

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-7016

**Body Style:** Straight shape, internal coupling Overall Length: 0.965 inches **Overall Diameter:** 0.445 inches **Environmental Protection:** Corrosion resistant and hermetic and shock resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 270.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold

**Shell Material Specification:** 

Qq-b-626 federal specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

## NSN 5935-01-100-7016

Electrical Plug Connector - Page 2 of 2



ncluded	Contact	Type:
---------	---------	-------

Coaxial pin single mating end single contact grouping

**Precious Material And Location:** 

Contact and body surfaces gold

**Precious Material And Weight:** 

0.105 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0