NSN 5935-01-100-7032



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-100-7032 **Overall Length:** 2.125 inches **Overall Height:** 2.000 inches Overall Width: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Mating End Quantity: Contact Position Arrangement Style:** 28-12 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 270.0 **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel **Included Contact Quantity:** 26 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping

Shelf Life: N/a

NSN 5935-01-100-7032

Electrical Receptacle Connector - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.