NSN 5935-01-100-8486

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-8486

| Thread Class: |
|--|
| |
| 2a Thread Direction. |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 0.870 inches |
| Overall Width: |
| 0.165 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end 1st contact grouping |
| Polarization Method: |
| Polarization boss and guide pin/socket |
| Connector Locking Method: |
| Screw |
| Thready Qty Per Inch (tpi): |
| 80 |
| Thread Size: |
| 0.060 inches |
| Terminal Location: |
| Back single mating end 1st contact grouping |
| Contact Material: |
| Copper alloy single mating end 1st contact grouping |
| Contact Surface Treatment: |
| Gold single mating end 1st contact grouping and copper single mating end 1st contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2 military specification 1st treatment response single mating end 1st contact grouping |
| Insert Material Specification: |
| Mil-m-14, ty sdg military specification single material response single mating end |
| Included Contact Quantity: |
| 24 single mating end 1st contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |

0.024 gold grains, troy

NSN 5935-01-100-8486

Electrical Plug Connector - Page 2 of 2



| Gold |
|---------------------------|
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.

Precious Material: