## NSN 5935-01-100-9658

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-9658

view Online at https://aerobasegroup.com/nsn/5935-01-100-9656					
Overall Length:					
1.215 inches					
Overall Height:					
1.266 inches					
Overall Width:					
1.266 inches					
Center To Center Distance Between Mounting Facilities Parallel To Height:					
0.938 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:					
0.938 inches					
Mating End Quantity:					
1					
Contact Position Arrangement Style:					
10-dec single mating end					
Contact Removability:					
Removable single mating end single contact grouping					
Contact Maximum Current Rating In Amps:					
10.0 single mating end single contact grouping					
Contact Maximum Ac Voltage Rating In Volts:					
500.0 single mating end single contact grouping					
Contact Maximum Dc Voltage Rating In Volts:					
700.0 single mating end single contact grouping					
Polarization Method:					
Keyway or multiple keyway					
Insert Position In Deg:					
60.0					
Shell Type:					
Solid					
Connector Locking Method:					
Bayonet latch					
Terminal Location:					
Back single mating end single contact grouping					
Terminal Type:					
Crimp single mating end single contact grouping					
Included Contact Quantity:					
10 single mating end single contact grouping					
Included Contact Type:					
Round socket single mating end single contact grouping					
Test Data Document:					
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification					
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain					
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).					

Shelf Life:

## NSN 5935-01-100-9658

Electrical Receptacle Connector - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.