NSN 5935-01-100-9660

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-100-9660

Overall Length:
1.215 inches
Overall Height:
1.266 inches
Overall Width:
1.266 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.938 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.938 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
10-dec single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
155.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 5935-01-100-9660

Electrical Receptacle Connector - Page 2 of 2



Ullit Ol Measure	U	Init	Of	Measure:	
------------------	---	------	----	----------	--

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.