

View Online at <https://aerobasegroup.com/nsn/5935-01-100-9679>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand

**Body Style:**

Rectangular shape

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.282 inches

**Overall Width:**

1.453 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.118 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.468 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

50 single mating end

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thread Length:**

0.320 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches and 0.138 inches

**Insert Material:**

Plastic diallyl phthalate single mating end

**Criticality Code Justification:**

Feat

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Special Features:**

Item must comply with requirements of desc production standard no. L02921; for navy nuclear propulsion plant product only

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.