# NSN 5935-01-101-2296

Thread Class: 2a and 2b and 2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-101-2296

Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.062 inches
Overall Height:
0.531 inches
Overall Width:
0.266 inches
Environmental Protection:
Moisture resistant and salt water resistant and thermal shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.814 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end

# NSN 5935-01-101-2296

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, class 1 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

20 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

0.020 gold grains, troy and 0.020 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.