

View Online at <https://aerobasegroup.com/nsn/5935-01-101-3936>

Thread Class:

2a and 2g

Thread Pitch Diameters:

+2.000/+2.011 inches

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.016 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Environmental Protection:

Humidity resistant and moisture resistant and corrosion resistant and chemical resistant and dust resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.203 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.688 inches

Distance From Mounting Shoulder To Front Face:

1.000 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-55 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

9.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

140.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 8

Thread Size:

1.613 inches and 2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.055 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Npt and acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0