Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-101-7808

Thread Class: 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 1.050 inches **Overall Diameter:** 0.469 inches **Environmental Protection:** Thermal shock resistant and moisture resistant and shock resistant and corrosion resistant **Mounting Facility Thickness:** 0.187 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Frequency Rating:** 500.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Radio Frequency Type Contact Characteristic Impedance In Ohms:** 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end



Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single

material response single mating end single contact grouping

Shell Material: Copper alloy Shell Surface Treatment:

Nickel and copper

Shell Surface Treatment Specification:

Qq-n-290 federal specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626, comp 1/2 h federal specification single material response

Insert Material Specification:

L-p-403 federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Triaxial socket single mating end single contact grouping

Special Features:

Furnished items - grounding lug

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.