Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-101-7814

Body Style:	
Straight shape	
Overall Length:	
Between 2.073 inches and 2.103 inches	
Overall Width:	
Between 0.479 inches and 0.509 inches	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Distance Between Mounting Facility Centers:	
1.852 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
25 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	
Terminal Location:	
Side single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and copper single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact group	ping and mil-c-14550, class 4
military specification 2nd treatment response single mating end single contact grouping	
Terminal Type:	
Pin single mating end single contact grouping	
Shell Material:	
Steel	
Shell Surface Treatment:	
Cadmium and chromate	
Insert Material Specification:	



Included Contact Quantity: 25 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Mtg bracket **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.025 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.