NSN 5935-01-101-7822

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-101-7822

Body Style:
Straight shape
Overall Length:
2.175 inches
Overall Width:
0.610 inches
Distance Between Mounting Facility Centers:
1.842 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
24 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Zinc and chromate
Insert Material Specification:
Mil-m-14f, type mdg military specification single material response single mating end

Included Contact Quantity:24 single mating end single contact grouping

NSN 5935-01-101-7822

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0

Mil-std (military Standard):

Mil-m-14f spec.