

View Online at <https://aerobasegroup.com/nsn/5935-01-102-6508>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.300 inches

Overall Height:

1.125 inches

Overall Width:

1.125 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

Between 0.708 inches and 0.728 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

"14-4, 14-04" single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

105.0 and 140.0 and 215.0 and 265.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

20

Thread Size:

0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-83723/72 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-15504