

View Online at <https://aerobasegroup.com/nsn/5935-01-102-7002>

Body Style:

Straight shape, internal coupling

Overall Diameter:

Between 1.860 inches and 1.920 inches

Environmental Protection:

Humidity resistant and salt water resistant and vibration proof

Mating End Quantity:

2

Contact Position Arrangement Style:

25-61 2nd mating end

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

Insert Material:

Plastic epoxy all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response 1st mating end single contact grouping

Criticality Code Justification:

Feat

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 military specification 2nd treatment response

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

61 2nd mating end single contact grouping

Included Contact Type:

Round socket 1st mating end single contact grouping

Special Features:

Used on weapons system ste-m1-fvs; 2050 ohm resistor attached between contacts ll and nn of connector p2 and a 953 ohm resistor attached between contacts mm and pp of connector p2

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.116 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.