

View Online at <https://aerobasegroup.com/nsn/5935-01-102-7002>

**Body Style:**

Straight shape, internal coupling

**Overall Diameter:**

Between 1.860 inches and 1.920 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and vibration proof

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

25-61 2nd mating end

**Contact Removability:**

Removable all mating ends single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet slot

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold 2nd mating end single contact grouping

**Insert Material:**

Plastic epoxy all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2 military specification single treatment response 1st mating end single contact grouping

**Criticality Code Justification:**

Feat

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and nickel

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 military specification 2nd treatment response

**Shell Material Specification:**

Qq-a-367 federal specification single material response

**Included Contact Quantity:**

61 2nd mating end single contact grouping

**Included Contact Type:**

Round socket 1st mating end single contact grouping

**Special Features:**

Used on weapons system ste-m1-fvs; 2050 ohm resistor attached between contacts ll and nn of connector p2 and a 953 ohm resistor attached between contacts mm and pp of connector p2

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.116 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.