

View Online at <https://aerobasegroup.com/nsn/5935-01-102-7019>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 7.750 inches and 8.500 inches

Overall Diameter:

1.900 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

25-61 2nd mating end

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1000.0 1st mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Operating Temperature Rating:

Between -55.0 degrees celsius and 200.0 degrees celsius

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

Insert Material:

Plastic epoxy 2nd mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response 1st mating end all contact groupings and qq-n-290, class 2 federal specification 2nd treatment response 1st mating end all contact groupings

Criticality Code Justification:

Feat

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response and mil-c-26074, class 3 or 4, grade b military specification 2nd treatment response

Included Contact Quantity:

61 2nd mating end single contact grouping

Included Contact Type:

Round pin all mating ends all contact groupings

Special Features:

Used on weapons system ste-m1-fvs; 1332 ohm resistor attached between contacts ll and mm of connector p2 and a 953 ohm resistor attached between contacts mm and pp of connector p2

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.102 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.