# NSN 5935-01-102-7117

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-102-7117

## Body Style:

Straight shape, external/internal coupling

## Overall Length:

Between 2.907 inches and 3.100 inches

## **Overall Diameter:**

1.430 inches

## **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

## Mating End Quantity:

#### 2

#### **Contact Position Arrangement Style:**

22-55 1st mating end25-61 2nd mating end

#### **Contact Removability:**

Removable all mating ends single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

1000.0 1st mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### Connector Locking Method:

Bayonet slot and bayonet slot

#### **Contact Material:**

Copper alloy all mating ends single contact grouping

#### **Contact Surface Treatment:**

Gold 1st mating end single contact grouping and nickel 1st mating end single contact groupinggold 2nd mating end single contact grouping **Insert Material:** 

Plastic 1st mating endplastic epoxy 2nd mating end

#### Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response 1st mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response 1st mating end single contact groupingmil-g-45204 military specification single treatment response 2nd mating end single contact grouping

#### Shell Material:

Plastic and aluminum alloy

#### Shell Surface Treatment:

Nickel

#### Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

#### **Included Contact Quantity:**

55 1st mating end single contact grouping61 2nd mating end single contact grouping

#### Included Contact Type:

Round pin all mating ends single contact grouping

## NSN 5935-01-102-7117

Connector Adapter - Page 2 of 2



**Precious Material And Location:** Contact surfaces gold Precious Material And Weight: 0.116 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.