

View Online at <https://aerobasegroup.com/nsn/5935-01-103-4749>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/clamp

Overall Height:

3.000 inches

Overall Diameter:

1.875 inches

Environmental Protection:

Watertight

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

450.0 single mating end single contact grouping

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.469 inches

Thready Qty Per Inch (tpi):

14

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic polycarbonate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

L-p-393 federal specification single material response single mating end

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-p-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-p-2726/55 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0