Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-103-4768

view Online at https://aerobasegroup.com/hsh/5955-01-105-4766
Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.185 inches
Overall Width:
0.305 inches
Distance Between Mounting Facility Centers:
0.965 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.