Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-103-8757

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.664 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.177 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Distance From Mounting Shoulder To Front Face:

0.850 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

22-7 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

10

Thread Size:

1.500 inches



Terminal Location:	
Back single mating e	nd single contact grouping
Contact Material:	
Copper alloy single r	nating end single contact grouping
Contact Surface Tr	eatment:
Gold single mating e	nd single contact grouping
Insert Material:	
Plastic single mating	end
Contact Surface Tr	eatment Specification:
Mil-g-45204, type 1	cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Solder well single m	ating end single contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface Treat	ment:
Cadmium and nickel	
Shell Surface Treat	ment Specification:
Qq-p-416, type 2 fe	deral specification 1st treatment response and qq-n-290 federal specification 2nd treatment response
Included Contact Q	uantity:
1 single mating end	single contact grouping
Included Contact T	ype:
Round socket single	mating end single contact grouping
Precious Material A	Ind Location:
Contact surface gold	
Precious Material A	nd Weight:
0.005 gold grains, tr	оу
Precious Material:	
Gold	
Thread Series Desi	gnator:
Double stub	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Sta	ndard):
Mil-g-45204 spec.	