## NSN 5935-01-103-9755

**Thread Class:** 

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-103-9755

20
Thread Direction:
Right-hand
Body Style:
Angle shape w/cable clamp
Overall Diameter:
1.968 inches
Body Angle In Deg:
45.0
Cable Entrance Diameter:
Between 0.611 inches and 0.938 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-20 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
3.048 inches
Distance From Centerline To Cable End:
2.376 inches
Thready Qty Per Inch (tpi):
18

## **NSN 5935-01-103-9755**Electrical Plug Connector - Page 2 of 2



Thread Size:
1.750 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
nsert Material:
Rubber synthetic single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
4 single mating end 2nd contact grouping
ncluded Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material:
Gold and silver
Thread Series Designator:
Jns
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
4039b0