

View Online at <https://aerobasegroup.com/nsn/5935-01-104-3855>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

1.656 inches

Overall Height:

1.656 inches

Overall Width:

0.812 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, cl 2 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response all mating ends single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 ty ii, cl 1 military specification single treatment response

Shell Material Specification:

Qq-s-763 condition a federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces and shell surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.