

View Online at <https://aerobasegroup.com/nsn/5935-01-104-4945>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

1.004 inches

Overall Height:

Between 1.850 inches and 1.870 inches

Overall Width:

Between 2.865 inches and 2.885 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.143 inches and 0.155 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.495 inches and 2.505 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

158 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Jackscrew

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

158 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Insert with mounting sleeve

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.158 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No