

View Online at <https://aerobasegroup.com/nsn/5935-01-104-6454>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

0.813 inches

Overall Diameter:

1.199 inches

Environmental Protection:

Moisture proof and salt water resistant and shock proof and vibration proof

Cable Entrance Diameter:

0.957 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Ik-I33 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Rubber silicone class q single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromium

Included Contact Quantity:

7 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.033 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0