

View Online at <https://aerobasegroup.com/nsn/5935-01-104-9212>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.405 inches

Overall Diameter:

Between 1.360 inches and 1.391 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Distance From Mounting Shoulder To Front Face:

Between 0.658 inches and 0.707 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.187 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

40515 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.290 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.750 inches and 0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Shell Material Specification:

Qq-a-367, t-6 federal specification single material response

Included Contact Quantity:

3 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

In order to complete the connector assembly, the user must obtain/provide the backshell; standard versions may be ordered as nsnn 5935-01-184-7189, p/n m85049/52-1-12w for the straight style, or nsnn 5935-01-181-6652, p/n m85049/51-1-12w for the right angle style

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3474 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

1-0001-0