

View Online at <https://aerobasegroup.com/nsn/5935-01-105-1192>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

3.970 inches

Overall Height:

3.375 inches

Overall Width:

3.375 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.281 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.812 inches

Distance From Mounting Shoulder To Front Face:

2.532 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

100.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.531 inches

Thready Qty Per Inch (tpi):

7

Thread Size:

3.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Oxide

Shell Surface Treatment Specification:

Mil-f-14072, e-516 military specification single treatment response

Included Contact Quantity:

2 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub

Specification Data:

96906-ms90555 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

1-0001-0

Mil-std (military Standard):

Mil-g-45204 spec.