Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-105-1378

| Body Style: |
|--|
| Wall type |
| Overall Width: |
| 1.750 inches |
| Body Length: |
| 2.875 inches |
| Environmental Protection: |
| Heat resistant and salt water resistant |
| Distance Between Mounting Facility Centers: |
| 3.281 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| "3, 6-20" single mating end |
| Contact Removability: |
| Removable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 20.0 single mating end all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 250.0 single mating end all contact groupings |
| Polarization Method: |
| Contact |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Terminal Type: |
| Screw single mating end all contact groupings |
| Included Contact Quantity: |
| 1 single mating end 3rd contact grouping |
| Included Contact Type: |
| T-socket single mating end 3rd contact grouping |
| Test Data Document: |
| 81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81348-w-c-596/64 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |