NSN 5935-01-105-5260



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-105-5260 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/backshell **Overall Length:** 1.234 inches **Overall Diameter:** 1.406 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell

Mating End Quantity:

Contact Position Arrangement Style:

17-8 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thready Qty Per Inch (tpi):

20

Thread Size:

0.938 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-105-5260

Mil-c-26074 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, cl 3 or 4, grade e military specification single treatment response
Included Contact Quantity:
8 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.008 gold grains, troy and 0.008 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27467 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):