Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-105-7922

Thread Class: 2a and 2a Thread Direction: Right-hand and right-hand Body Style: Straight shape, external coupling Overall Length: 1.437 inches Distance From Mounting Shoulder To Front Face: 0.675 inches Mounting Facility Thickness: 0.125 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp
Thread Direction: Right-hand and right-hand Body Style: Straight shape, external coupling Overall Length: 1.437 inches Distance From Mounting Shoulder To Front Face: 0.675 inches Mounting Facility Thickness: 0.675 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Thre single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut
Right-hand and right-handBody Style:Straight shape, external couplingOverall Length:1.437 inchesDistance From Mounting Shoulder To Front Face:0.675 inchesMounting Facility Thickness:0.125 inchesThreaded Device Type:Coupling facility and mounting bushingMating End Quantity:1Contact Position Arrangement Style:Thre single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidConnector Locking Method:Externally threaded coupling nutConnector Cable Strain Relief Method:
Body Style: Straight shape, external coupling Overall Length: 1.437 inches Distance From Mounting Shoulder To Front Face: 0.675 inches Mounting Facility Thickness: 0.125 inches Motted Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Straight shape, external coupling Overall Length: 1.437 inches Distance From Mounting Shoulder To Front Face: 0.675 inches Mounting Facility Thickness: 0.675 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Thc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Overall Length:1.437 inchesDistance From Mounting Shoulder To Front Face:0.675 inchesMounting Facility Thickness:0.125 inchesThreaded Device Type:Coupling facility and mounting bushingMating End Quantity:1Contact Position Arrangement Style:Tnc single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidConnector Locking Method:Externally threaded coupling nutConnector Cable Strain Relief Method:
1.437 inches Distance From Mounting Shoulder To Front Face: 0.675 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut
Distance From Mounting Shoulder To Front Face:0.675 inchesMounting Facility Thickness:0.125 inchesThreaded Device Type:Coupling facility and mounting bushingMating End Quantity:1Contact Position Arrangement Style:Tnc single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidConnector Locking Method:Externally threaded coupling nutConnector Cable Strain Relief Method:
0.675 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Mounting Facility Thickness: 0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
0.125 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Mating End Quantity: 1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
1 Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Contact Position Arrangement Style: Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Tnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Shell Type: Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Solid Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Connector Locking Method: Externally threaded coupling nut Connector Cable Strain Relief Method:
Externally threaded coupling nut Connector Cable Strain Relief Method:
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
28 and 28
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
i oniniai i jpoi
Solder well single mating end single contact grouping
Solder well single mating end single contact grouping
Solder well single mating end single contact grouping Included Contact Quantity:
Solder well single mating end single contact grouping Included Contact Quantity: 1 single mating end single contact grouping
Solder well single mating end single contact grouping Included Contact Quantity: 1 single mating end single contact grouping Bushing Accommodation Hole Shape:
Solder well single mating end single contact grouping Included Contact Quantity: 1 single mating end single contact grouping Bushing Accommodation Hole Shape: Round

Unef and unef

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0