## NSN 5935-01-105-8121

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-105-8121

Thread Class:
2a and 2b and 2b
Thread Direction:
Right-hand
Body Style:
T-shape
Overall Length:
1.000 inches
Overall Height:
0.900 inches
Overall Width:
0.688 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
3
Contact Position Arrangement Style:
Sma all mating ends
Contact Removability:
Removable all mating ends all contact groupings
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell and internally threaded coupling ring
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends all contact groupings
End Application:
Strategic weapon systems
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 2, grade c military specification single treatment response all mating ends all contact groupings
Shell Material:

Copper alloy

## NSN 5935-01-105-8121

Connector Adapter - Page 2 of 2

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.



Included Contact Quantity:
1 2nd mating end all contact groupings
Included Contact Type:
Coaxial socket 2nd mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-a-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
81349-mil-a-55339/30 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: