## NSN 5935-01-105-8413

**Body Style:** 

**Overall Length:** 

**Test Data Document:** 

Straight shape, flange mount

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-105-8413

2.062 inches
Bushing Diameter:
1.328 inches
Overall Height:
1.437 inches
Environmental Protection:
Heat resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
1.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"3, 5-15" single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
15.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
125.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
125.0 single mating end all contact groupings
Polarization Method:
Contact
Shell Type:
Solid
Terminal Location:
Side single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Terminal Type:
Screw single mating end all contact groupings
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
U-pin single mating end 1st contact grouping

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5935-01-105-8413

Electrical Receptacle Connector - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81348-w-c-596/140 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0